

TYPE	POWER KW	HORSEPOWER HP	VOLTAGE V	CURRENT A	FREQUENCY HZ	SPEED R/MIN	EFFICIENCY %	POWER FACTOR COS	LOCKED-ROTOR CURRENT/RATED CURRENT	LOCKED - ROTOR TORQUE/RATED TORQUE	MAX TORQUE/RATED TORQUE	NOISE LwdB(A)
Y2-631-2	0.18	0.25	380	0.5	50	2800	65	0.8	5.5	2.2	2.2	61
Y2-632-2	0.25	0.33	380	0.7	50	2800	68	0.81	5.5	2.2	2.2	61
Y2-711-2	0.37	0.05	380	1	50	2800	70	0.81	6.1	2	2.2	64
Y2-712-2	0.55	0.75	380	1.4	50	2800	73	0.82	6.1	2.2	2.3	64
Y2-801-2	0.75	1	380	1.8	50	2825	75	0.83	6.1	2.2	2.3	67
Y2-802-2	1.1	1.5	380	2.6	50	2825	77	0.84	7	2.2	2.3	67
Y2-90S-2	1.5	2	380	3.4	50	2840	79	0.84	7	2.2	2.3	72
Y2-90L-2	2.2	3	380	4.9	50	2840	81	0.85	7	2.2	2.3	72
Y2-100L-2	3	4	380	6.3	50	2880	83	0.87	7.5	2.2	2.3	76
Y2-112M-2	4	5.5	380	8.1	50	2890	85	0.88	7.5	2.2	2.3	77
Y2-132S1-2	5.5	7.5	380	11	50	2900	86	0.88	7.5	2.2	2.3	80
Y2-132S2-2	7.5	10	380	14.9	50	2900	87	0.88	7.5	2.2	2.3	80
Y2-160M1-2	11	15	380	21	50	2930	88	0.89	7.5	2.2	2.3	86
Y2-160M-2	15	20	380	29	50	2930	89	0.89	7.5	2.2	2.3	86
Y2-160L-2	18.5	25	380	35	50	2930	90	0.9	7.5	2.2	2.3	86
Y2-180M-2	22	30	380	41	50	2940	90	0.9	7.5	2.2	2.3	89
Y2-200L1-2	30	40	380	55	50	2950	91.2	0.9	7.5	2	2.3	92
Y2-200L2-2	37	50	380	68	50	2950	92	0.9	7.5	2	2.3	92
Y2-225M-2	45	60	380	82	50	2970	92.3	0.9	7.5	2	2.3	92
Y2-631-4	0.12	0.16	380	0.4	50	1400	57	0.72	4.4	2.1	2.2	52
Y2-632-4	0.18	0.25	380	0.6	50	1400	60	0.73	4.4	2.1	2.2	52
Y2-711-4	0.25	0.33	380	0.8	50	1400	65	0.74	5.2	2.1	2.2	55
Y2-712-4	0.37	0.5	380	1.1	50	1400	67	0.75	5.2	2.1	2.3	55
Y2-801-4	0.55	0.75	380	1.6	50	1390	71	0.75	5.2	2.3	2.3	58
Y2-802-4	0.75	1	380	2	50	1390	73	0.77	6	2.3	2.3	58
Y2-90S-4	1.1	1.5	380	2.9	50	1400	75	0.77	6	2.3	2.3	61
Y2-90L-4	1.5	2	380	3.7	50	1400	78	0.79	6	2.3	2.3	61
Y2-100L1-4	2.2	3	380	5.2	50	1420	80	0.81	7	2.3	2.3	64
Y2-100L2-4	3	4	380	6.8	50	1420	82	0.82	7	2.3	2.3	64
Y2-112M-4	4	5.5	380	8.8	50	1440	84	0.82	7	2.3	2.3	65
Y2-132S-4	5.5	7.5	380	11.8	50	1440	85	0.83	7	2.3	2.3	71
Y2-132M-4	7.5	10	380	15.6	50	1440	87	0.84	7	2.3	2.3	71
Y2-160M-4	11	15	380	22	50	1460	88	0.84	7	2.3	2.3	75
Y2-160L-4	15	20	380	30	50	1460	89	0.85	7.5	2.3	2.3	75
Y2-180M-4	18.5	25	380	36	50	1470	90.5	0.86	7.5	2.2	2.3	76
Y2-180L-4	22	30	380	43	50	1470	91	0.86	7.5	2.2	2.3	76
Y2-200L-4	30	40	380	58	50	1480	92	0.86	7.2	2.2	2.3	79
Y2-225S-4	37	50	380	70	50	1480	92.5	0.87	7.2	2.2	2.3	81
Y2-225M-4	45	60	380	85	50	1480	92.8	0.87	7.2	2.2	2.3	81
Y2-711-6	0.18	0.25	380	0.8	50	900	56	0.66	4	1.9	2.3	52
Y2-712-6	0.25	0.33	380	0.9	50	900	59	0.68	4	1.9	2	52
Y2-801-6	0.37	0.5	380	1.3	50	900	62	0.7	4.7	1.9	2	54
Y2-802-6	0.55	0.75	380	1.8	50	900	65	0.72	4.7	1.9	2.1	54
Y2-90S-6	0.75	1	380	2.3	50	910	69	0.72	5.5	2	2.1	57
Y2-90L-6	1.1	1.5	380	3.2	50	910	72	0.73	5.5	2	2.1	57
Y2-100L-6	1.5	2	380	3.9	50	940	76	0.76	5.5	2	2.1	61
Y2-112M-6	2.2	3	380	5.6	50	940	79	0.76	6.5	2.1	2.1	65
Y2-132S-6	3	4	380	7.4	50	960	81	0.76	6.5	2.1	2.1	69
Y2-132M1-6	4	5.5	380	9.9	50	960	82	0.76	6.5	2.1	2.1	69
Y2-132M2-6	5.5	7.5	380	12.9	50	960	84	0.77	6.5	2.1	2.1	69
Y2-160M-6	7.5	10	380	16.9	50	970	86	0.77	6.5	2	2.1	73
Y2-160L-6	11	15	380	24	50	970	87.5	0.78	6.5	2	2.1	73
Y2-180L-6	15	20	380	32	50	970	89	0.81	7	2	2.1	73
Y2-200L1-6	15	25	380	39	50	970	90	0.81	7	2.1	2.1	76
Y2-200L2-6	22	30	380	45	50	970	90	0.83	7	2.1	2.1	76
Y2-225M-6	30	40	380	59	50	980	91.5	0.84	7	2	2.1	76
Y2-801-8	0.18	0.25	380	0.9	50	690	51	0.61	3.3	1.8	1.9	52
Y2-802-8	0.25	0.33	380	1.2	50	690	54	0.61	3.3	1.8	1.9	52
Y2-90S-8	0.37	0.5	380	1.5	50	690	62	0.61	4	1.8	1.9	56
Y2-90L-8	0.55	0.75	380	2.2	50	690	63	0.61	4	1.8	2	56
Y2-100L1-8	0.75	1	380	2.4	50	700	71	0.67	4	1.8	2	59
Y2-100L2-8	1	1.5	380	3.3	50	700	73	0.69	5	1.8	2	59
Y2-112M-8	1.5	2	380	4.4	50	700	75	0.68	5	1.8	2	61
Y2-132S-8	2.2	3	380	6	50	710	78	0.71	6	1.8	2	64
Y2-132M-8	3	4	380	7.9	50	710	79	0.73	6	1.8	2	64
Y2-160M1-8	4	5.5	380	10.3	50	720	81	0.73	5.5	2	2	68
Y2-160M2-8	5.5	7.5	380	13.6	50	720	83	0.74	6	2	2	68
Y2-160L-8	7.5	10	380	17.8	50	720	85.5	0.75	6	2	2	68
Y2-200L-8	15	20	380	34	50	730	88	0.76	6	2	2	73
Y2-225S-8	18.5	25	380	41	50	730	90	0.76	6	1.9	2	73
Y2-225M-8	22	30	380	47	50	730	90.5	0.78	6	1.9	2	73